

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method for processing queries of hierarchical tagged data using hints, said hints being navigational aids and said processing being performed on a computing device, the method comprising:

providing a plurality of hints for the hierarchical tagged data, said data having a plurality of nodes l and c such that l is a parent of c ;

pruning the hierarchical tagged data using said plurality of hints to avoid unnecessary navigation when processing said queries;

updating said hints in accordance with required navigation workload and updates and changes to the hierarchical tagged data;

providing a usefulness matrix for calculating a usefulness of each of said hints, wherein for a pre-defined parameter $0 \leq \alpha \leq 1$, the usefulness of the hint is calculated as $Usf_{h(l,c,t)} = (1 + \alpha \times semW_{h(l,c,t)}) \times Usf_{h(l,c,t)}$, where $semW_{h(l,c,t)}$ is a semantic weight and $sUsf_{h(l,c,t)}$ is a structural usefulness of the hint; and

selecting techniques for hints according to limitations on an allocated memory size of said computing device.

2. (Original) The method of claim 1, wherein the hint being represented as $h(l, c, t)$, where t is a tag of a child node accessible in top-down traversal from c , said hint being positive if t exists and otherwise negative.

3. (Currently Amended) The method of claim 1, further comprising the steps of:
matching hint information at a currently accessed node n with a remaining query

path q ;

analyzing all hints where c is a child of node n ; and

eliminating from future query processing a sub tree rooted at each child c of node n having a tag t .

4. (Currently Amended) The method of claim 1, further comprising the steps of:

- a) for every query path q , identifying all children c of a current node n having a tag t ~~to be visited in a next step of query processing~~;
- b) for each tag t to match in said query path q , determining all hints such that c is a child of n ;
- c) eliminating from query all said children c of said current node n having said tag t ~~to be visited in said next step of query processing~~;
- d) determining a query constraints and further reducing said children c having said tag t ~~to be visited in said next step of query processing~~ in accordance with said constraints;
- e) for each said child c having said tag t , setting sub queries q' corresponding to a sub tree rooted at said child c having said tag t , and
- f) repeating steps (a) through (e).

5. (Currently Amended) A method of utilizing one or more hints for query processing over a hierarchical tagged data structure in a computing system having memory, the data structure having a plurality of nodes l and c such that l is a parent of c , the hint, represented as $h(l, c, t)$, being positive if there is a tag t accessible in top-down traversal from c and otherwise negative, said method comprising steps of:

- for each tag in the XML document, the computing system:
- calculating each hint and a usefulness of each hint;
- selecting a number of hints k having a greatest usefulness, where k equals a total memory size divided by a size of the hint;
- providing a usefulness matrix for calculating the usefulness of each of said hints, wherein for a pre-defined parameter $0 \leq \alpha \leq 1$, the usefulness of the hint is calculated as $Usf_{h(l,c,t)} = (1 + \alpha \times semW_{h(l,c,t)}) \times Usf_{h(l,c,t)}$, where $semW_{h(l,c,t)}$ is a semantic weight and $sUsf_{h(l,c,t)}$ is a structural usefulness of the hint; and
- eliminating redundant hints.

6. (Cancelled)

7. (Currently Amended) The method of claim 6, wherein said structural usefulness of a the hint is corresponds with a number of nodes of said data structure that can be pruned out the search space for a query “//t” if the hint is materialized.

8. (Original) The method of claim 5, wherein only negative hints are used.

9. (Currently Amended) A method of utilizing one or more hints for query processing over a hierarchical tagged data structure in a computing system having memory, the data structure having a plurality of nodes l and c such that l is a parent of c , the hint, represented as $h(l, c, t)$, being positive if there is a tag t accessible in top-down traversal from a child node and otherwise negative, said method comprising steps of:

for each tag in the data structure, the computing system:

- (a) calculating a bitmap for a current node $B(current)$ with all bits set to one;
- (b) setting a bit of a current tag $B(current)[tag(current-tag)]$ to zero;
- (c) calculating a plurality of possible non-redundant hints for each child node; ~~and~~
- (d) refreshing a hint list; and
- (e) providing a usefulness matrix for calculating a usefulness of each of said hints,

wherein for a pre-defined parameter $0 \leq \alpha \leq 1$, the usefulness of the hint is calculated as $Usf_{h(l,c,t)}$
 $= (1 + \alpha \times semW_{h(l,c,t)}) \times Usf_{h(l,c,t)}$, where $semW_{h(l,c,t)}$ is a semantic weight and $sUsf_{h(l,c,t)}$ is a
structural usefulness of the hint.

10. (Original) The method of claim 9, wherein step (a) further comprises the steps of:
calculating a bitmap for each child node of said current node;
AND-ing all said bitmaps for each child node; and
setting a bit corresponding to tag ID $B(current)[tagid(current - tag)]$ of a current tag to zero if said current tag exists.

11. (Original) The method of claim 9, wherein step (c) further comprises the steps of:
for each bit j such that $B(current)[j]$ is equal to zero and $B(child)[j]$ is equal to one:
(c1) determining if there is a need to add a hint $h(current\ node, current\ child, tag(j))$ to a

list of hints;

- (c2) eliminating a least useful hint from said list if said list is full; and
- (c3) adding said hint to said list.

12. (Original) The method of claim 11, wherein step (c1) further comprises the step of determining if a usefulness value $Usf[h(current\ node, current\ child, tag(j))]$ of said hint is greater than the least useful hint in said list.

13. (Original) The method of claim 9, wherein only negative hints are used.

14. (Currently Amended) A computer program device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for utilizing one or more hints for query processing over a hierarchical tagged data structure in a computing system having memory, the data structure having a plurality of nodes l and c such that l is a parent of c , the hint, represented as $h(l, c, t)$, being positive if there is a tag accessible in top-down traversal from a child node, and otherwise negative, said method comprising steps of:

for each tag in the data structure, the machine using the computer program device for:

- (a) calculating a bitmap for a current node $B(current)$ with all bits set to 1;
- (b) setting a bit of a current tag $B(current)[tag(current-tag)]$ to zero;
- (c) calculating a plurality of possible non-redundant hints for each child node; ~~and~~
- (d) refreshing a hint list; and
- (e) providing a usefulness matrix for calculating a usefulness of each of said hints,

wherein for a pre-defined parameter $0 \leq \alpha \leq 1$, the usefulness of the hint is calculated as $Usf_{h(l,c,t)}$
 $= (1 + \alpha \times semW_{h(l,c,t)}) \times Usf_{h(l,c,t)}$, where $semW_{h(l,c,t)}$ is a semantic weight and $sUsf_{h(l,c,t)}$ is a
structural usefulness of the hint.

15. (Original) The method of claim 14, wherein step (a) further comprises the steps of:
calculating a bitmap for each child node of said current node;
AND-ing all said bitmaps for each child node; and
setting a bit corresponding to tag ID $B(current)[tagid(current - tag)]$ of a current tag to

zero if said current tag exists.

16. (Original) The method of claim 14, wherein step (c) further comprises the steps of:
for each bit j such that $B(\text{current})[j]$ is equal to zero and $B(\text{child})[j]$ is equal to one
(c1) determining if there is a need to add a hint $h(\text{current node}, \text{current child}, \text{tag}(j))$ to a list of hints;
(c2) eliminating a least useful hint from said list if said list is full; and
(c3) adding said hint to said list.

17. (Original) The method of claim 16, wherein step (c1) further comprises the step of determining if a usefulness value $Usf[h(\text{current node}, \text{current child}, \text{tag}(j))]$ of said hint is greater than the least useful hint in said list.

18. (Original) The method of claim 15, wherein only negative hints are used.